

Super Micro Bell Sprayer

Model: SUPER65

The super micro bell sprayer allows the application of liquid solvent-based or water-based paint in general industry. Known as the best rotary bell sprayer, Super65 benefits from technologies developed for automotive markets. It is usually used with a reciprocating machine or in fixed station.

Features

- High transfer efficiency (up to 80%)
- Super gloss and regularity of film build
- Easy and fast maintenance
- Suitable water-based and solvent-based paint

Field of Application

- Metallic furniture
- Wood furniture
- Cycles & Motorcycles
- Agricultural & construction equipment



SPECIFICATIONS

Rotation speed max.	45000 rpm
Operating air pressure max.	6 bars (90 psi)
Normal pilot air	6 to 10 bars (90 to 150 psi)
Magnetic bearing air pressure	7 bars (105 psi)
Amount of air bearing backup	25 liters - 6 bars (90 psi)
Total air consumption	20 to 45 Nm ³ /h
Fluid pressure max.	10 bars (150 psi)
Paint flow	30 to 400 cc/min
Viscosity range, Coupe FORD n ° 4	15 to 45 seconds
Voltage max.	90 KV (Option)
Current max.	100 µA
Weight (without cable and hose)	1.92 kg
SUPER65	with 3 - 2 way micro valve

