

Manual Electrostatic Spray Gun

手持靜電噴槍 MEG-100

特性 / Character

- Light-weighted, simple operation, high safety, durable, saving a large amount of paint, suitable for a variety of coating .
重量輕，操作方便，安全性高，耐久性長，節省大量塗料，適用於各種導電工作塗裝。
- Electric current can be properly adjusted depending on the electric conduction of the coating . 可依塗料導電不同，適當調整電流。
- Large adjusting range of high voltage output meets a wide range of applications.
高壓電輸出調整範圍大，適用廣泛。
- Two steps of the alarm output indicate the status of coating material, and avoid abnormal coating. 警報音響有兩段輸出，可預知噴塗情形，避免不正常使用。
- Fan-shaped nozzle or round nozzle can be used to meet the coating requirements of various materials. 可以搭配扇型噴嘴或圓型噴嘴，以符合各種材質的噴塗須求。



高壓產生器規格表 / H.V Electrostatic specification:

使用電壓 Voltage used	110 VAC or 220 VAC - Ø2 Switch
無負荷電壓 Non-load voltage	DC-70 KV
定格輸出 Rated output	DC-60 KV / 50 μ A
輸出調整 Output adjustment	Non-step adjustment
輸出方式 Output	Air pressure control switch
過電流跳脫時間 Trip time of over-current	1/100 sec. Discharge time \leq 3 sec
消耗功率 Power consumption	\leq 250 W
最低啟動氣壓 Min. starting air pressure	2.5 kg/cm ²
尺寸 Size	200 m/m x 158 m/m x 240 m/m
淨重 Net weight	8.2 kgs

Gold River



靜電噴槍規格表 / Manual Electrostatic Spray Gun specification:

高壓輸出調整 / H.V output adjust	0-60 KV
最大使用塗量 / Max. spray flow	300 ml/min
最高傳遞效率 / Max. Transfer Efficiency(%)	85%
槍身長度 / Length	270 mm
槍身淨重 / Net Weight	0.5 kg

噴嘴規格表 / Specifications of nozzle:

噴嘴型式 Nozzle type	M-TYPE 圓吹噴嘴 Round nozzle	A-TYPE 圓吹噴嘴 Round nozzle	S-TYPE 圓吹噴嘴 Round nozzle	R-TYPE 圓吹噴嘴 Round nozzle	F-TYPE 扇型平吹噴嘴 Fan-shaped nozzle
空氣消耗量 (L / min) Air consumption	180	180	135	120	350
噴漆流量 (ml/min) Spray flow	20-300	20-300	15-225	15-220	50-300
霧化壓力 (kg / cm ²) Atomizing pressure	1.5-3.2	1.5-3.2	1.5-3.2	2-3.5	2.5-4
噴幅 (mm) Spray pattern	Ø80~Ø160 300	Ø80~Ø160 300	Ø50~Ø120 300	Ø75 220	40-250
照片 Photo					

噴嘴特性及用途 / Characters and applications of the nozzle:

M-TYPE	用於塗料帶有粉粒，如色粉或銀粉，寬幅大、霧化一般。 Suitable for coating material with powder, like color powder or silver powder; wider spray pattern like atomizing.
A-TYPE	用於透明塗料，幅大、速度快、霧化良好。 Suitable for transparent coating material; wider spray pattern, fast spray speed, good atomizing.
S-TYPE	用於小型且透明塗料，寬幅小，可節省塗料。 Suitable for the transparent coating material to paint small area; narrower spray pattern to save coating material.
R-TYPE	用於木器透明塗噴塗，寬幅固定、霧化良好、噴頭不易損壞。 Suitable for transparent paint (top coat) on wooden furniture; great atomizing; spray nozzle durable.
F-TYPE	用於大面積噴塗，如：桌面等。快速且工作效率高。 Suitable for painting large area, such as table top; fast painting and high efficiency.

Gold River